



Sea-R.O., Inc. Watermakers

Fresh water pumps

By Goul ds



Goulds JS+ series shallow well jet pumps are used to provide fresh water system pressure from a source such as shallow wells, cisterns, and storage tanks. Pumps include pressure switch to automatically turn pump on when system pressure drops below 30psi and pump will continue to run until pressure reaches 50psi, then shuts off. Compact design has an integral shallow well adapter built into the casing that allows maximum suction lift of 25'. Back pull out design allows pump to be serviced without disturbing piping. Impellers is glass filled Noryl and is corrosion and abrasion resistant. Unique design retains water in the casing at all times to ensure the mechanical seal can never run dry. Excellent air handling ability allows the pump to re-prime even if air gets in system. Cast iron casing is electro-coated inside and out with baked on finish for corrosion resistance. Should be used with accumulator tank.

Model/HP	Discharge psi/gpm	Weight/Length	Price
J5S/1/2hp	20/17.5, 30/16.5, 40/10.2, 50/5.0	43lbs/17-1/4"	\$374.00
J5SH/1/2hp	30/11.3, 40/11.0, 50/7.7, 60/4.8	43lbs/17-1/4"	\$374.00
J7S/3/4hp	30/21.3, 40/18.3, 50/12.5, 60/6.6	47lbs/18-1/4"	\$460.00
J10S/1.0hp	30/24.8, 40/24.4, 50/16.6, 60/9.9	50lbs/18-3/4"	\$505.00
J15S/1.5hp	30/26.6, 40/26.3, 50/25.0, 60/15.6	60lbs/19-1/4"	\$651.00

All pump models measure 9-7/8" width, 8-3/4" height. Above pressures and flows are based on suction lift of 5'. Complete specifications and performance ratings are available. Exploded drawings and all service parts are also available.