



Sea-R.O., Inc. Watermakers All 316 Stainless Steel Glycerine filled Pressure Gauges



Sea-R.O., offers a complete line of pressure gauges made exclusively from all 316SS wetted parts. Ideal for seawater and corrosive environments. Glycerine filled gauges dampen pulsations for a smooth steady reading. Gauges are available in either bottom mount connection or back mounted version that can also be panel mounted with bracket shown above. All gauges have 1/4" male NPT fitting as standard connection.

Standard pressure ranges: 0-30, 0-60, 0-100, and 0-1000 psi.

2.5" dial size standard. 4" available special order

Model	Description	Pressure range	Price
4154GXX30	2.5" gauge bottom mount	0-30psi	\$39.50
4154GXX60	2.5" gauge bottom mount	0-60psi	\$39.50
4154GXX100	2.5" gauge bottom mount	0-100psi	\$39.50
4154GXX1000	2.5" gauge bottom mount	0-1000psi	\$39.50
4254GXX30	2.5" gauge back mount	0-30psi	\$49.50
4254GXX60	2.5" gauge back mount	0-60psi	\$49.50
4254GXX100	2.5" gauge back mount	0-100psi	\$49.50
4254GXX1000	2.5" gauge back mount	0-1000psi	\$49.50

Specifications: Movement 316SS, Bourdon tube 316SS, Pointer Black enameled aluminum, Dial White aluminum, Window polycarbonate, Case material 304SS, Connection material 316SS, Connection size 1/4" MNPT, Accuracy ASME/ANSI B40.1 Grade B (3-2-3%)